

WareDose 10 is a very small sized, easy to use, dosing system in a new SEKO outlook, with LED display, using potentiometers settings.

### FEATURES



- **Switching power supply** 100÷240 Vac @50/60 Hz
- **IP65** Protection degree and class II electrical insulation
- **ON/OFF** switch
- **Level Control Inputs**
- **Analog Speed Control (15-100%)** of Det and Rinse pump via potentiometer on the board
- **Manual Priming** of the pumps via buttons on frontal panel
- Features **new PC front cover with easy opening and stop in open position**
- Robust PP enclosure with easy opening by frontal screws
- Robust plastic bracket with safety hook to lock the device in position
- Extremely compact size for maximum space saving in the kitchen (device surface reduced by 30%)

### TECHNICAL FEATURES

<b>TYPE</b>	WareDose 10 Kompact
<b>CODE</b>	WDC10040100M0000
<b>CERTIFICATIONS</b>	CE, EAC
<b>INTERFACE</b>	Analogue with LED display
<b>PROTECTION DEGREE</b>	IP65
<b>ELECTRICAL CLASS</b>	Class II (ground connection not needed)
<b>POWER SUPPLY</b>	100÷240 Vac @50/60 Hz
<b>CONSUMPTION</b>	10 W
<b>OPERATING TEMPERATURE</b>	10-50°C
<b>STORAGE TEMPERATURE</b>	-20÷60°C
<b>CASE MATERIAL</b>	Polypropylene

### HYDRAULIC DATA

<b>DETERGENT PUMP FLOW RATE</b>	1 - 4 l/h
<b>RINSE AID PUMP FLOW RATE</b>	0,15 – 1 l/h
<b>RINSE PUMP MAX WORKING BACKPRESSURE</b>	3 bar
<b>DETERGENT PUMP SQUEEZE TUBE</b>	Santoprene (6x10)
<b>RINSE PUMP SQUEEZE TUBE</b>	Sekobril (3x8)
<b>EXTERNAL TUBE FITTINGS</b>	For tube 4x6 with nuts (others upon request)

### DIMENSIONS

